



Recommended PCB Layout  
(Top View)

**Material and Finish**

Shell: Steel, nickel plated  
 Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated  
 Color: Black

Contact Material:  
 Socket - Brass

Contact Plating Options:  
 Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact

15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact

30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

**Electrical Specifications**

Rated Current: 1.5A  
 Rated Voltage: 30Vac  
 Insulation Resistance: more than 1000 megohms at 500V DC  
 Contact Resistance: 13 milliohms max.  
 Dielectric Withstanding Voltage: 1000V for 1 minute  
 Operating Temperature: -55°C to +75°C

Ordering Information	
Part Number	Contact Area Plating Finish
K86X-CD-62S-K	Gold Flash (standard option)
K86X-CD-62S-K15	15u" Gold (15 option)
K86X-CD-62S-K30	30u" Gold (30 option)

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated
Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	5/3/07	New Drawing	A. Frederick	H. MA	A. Frederick	5/3/07
A2	1/16/08	ECO# 07-052	WILL H.	H. MA		
A3	9/23/14	ECO#14-028	H. MA	P. DalCanto		
A4	12/31/17	ECO #17-033	J. Elbanna	C. Furumasu		
A5	01/17/23	Correct Shell Height to 5.8	C. Kelleher	C. Furumasu		

**K86X-CD-62S-K**

Vertical D-Sub, RoHS Compliant  
 62 pin, Socket with K Option

