


Recommended PCB Layout  
(Bottom View)



Part Number	Center Pin Diameter
KLDVX-0202-A	Ø2.00
KLDVX-0202-B	Ø2.50
KLDVX-0202-D	Ø3.00

**Material and Finish**

- Body: High Temp Material  
UL94V-0 Rated, Color: Black
- Center Pin: Brass, Nickel Plated
- Contact #1: Brass, Matte Tin Plated
- Contact #2:  
Phosphor Bronze, Matte Tin Plated
- Contact #3: Brass, Matte Tin Plated

**Electrical Characteristics**

- Rated Voltage: 24V DC
- Rated Current: 3.5 Amps
- Contact Resistance  
Before Test  
Between Terminals: 30 milliohms Max.  
Plug to Contacts: 50 milliohms Max.  
After Test:  
Between Terminals: 60 milliohms Max.  
Plug to Contacts: 100 milliohms Max.
- Insulation Resistance: 100 Megohms Min. (initial)  
50 Megohms Min. (after humidity test)
- Dielectric Withstanding Voltage:  
500V AC for 1 minute

**Mechanical Characteristics**

- Durability Test: 5000 cycles
- Insertion Force: 0.3kg-2.0kg
- Extraction Force: 0.3kg-2.0kg
- Operating Temp: -25°C to +85°C

Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated
Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A5	10/18/10	ECO #10-072	S. Vien	H. MA	H. MA	7/6/05
A6	07/26/11	ECO #11-051	S. Vien	H. MA		
A7	06/20/13	ECO #13-041	W. Cook	P. DalCanto	UNITS	mm
A8	03/23/18	ECO #18-015	H. MA	C. Furumasu		
A9	12/05/18	ECO #18-062	D. Shehan	G. Serrato		
A10	02/12/21	ECO #21-003	C. Kelleher	C. Furumasu		

**KLDVX-0202-x**

Power Jack, Vertical, PCB Mount, RoHS compliant  
Ø2.0mm, Ø2.5mm & Ø3.0mm Center Pin, High Temp

