

Materials and Finish

Housing: Polycarbonate,
UL 94V-2 Rated
Contact Material:
Copper Alloy
Plating Options:
1000 Series:
Gold Flash over 100u" Nickel
Underplate
5000 Series:
50u" Gold over 100u" Nickel
to Comply with ANSI/TIA-1096-A
Shield: Copper Alloy, Nickel Plated

Electrical Characteristics

Rated Current: 1.5A
Insulation Resistance:
500 Megohms Min.
Contact Resistance:
20 milliohms Max.
Dielectric Withstanding Voltage:
1000V AC for 1 Minute

Mechanical Characteristics

Operating Temperature:
-55°C to +85°C

Part Number	Contact Area Plating Finish
MPS88RX-1000S	Gold Flash (1000 Option)
MPS88RX-5000S	50u" Gold (5000 Option)




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	10/18/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	9/21/05
A1	03/25/11	Remove Prelim	S. Vien	H. MA		
A2	02/06/13	ECO #12-068	S. Vien	P. DalCanto		
A3	05/29/15	ECO #15-029	H. MA	W. Cook		

MPS88RX-xxxxS
xxxx = contact plating option

Shielded Modular Plug, RoHS Compliant

8 Position, 8 Contact, Round Cable Jacket, Solid Wire



UNITS
mm