

Materials and Finish

Housing: Polycarbonate,
UL 94V-2 Rated

Contact Material:
Copper Alloy

Plating Options:

1000 Series:
Gold Flash over 100u" Nickel
Underplate

5000 Series:
50u" Gold over 100u" Nickel
to Comply with ANSI/TIA-1096-A

Shield: Copper Alloy, Nickel Plated

Electrical Characteristics

Rated Current: 1.5A

Insulation Resistance:
500 Megohms Min.

Contact Resistance:
20 milliohms Max.

Dielectric Withstanding Voltage:
1000V AC for 1 Minute

Mechanical Characteristics

Operating Temperature:
-55°C to +85°C

Part Number	Contact Area Plating Finish
MPS88X-1000	Gold Flash (1000 Option)
MPS88X-5000	50u" Gold (5000 Option)

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise




REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	08/15/05	New Drawing	R. Aguirre	N.Chang	R. Aguirre	8/15/05
A2	02/06/13	ECO #12-068	S. Vien	P. DalCanto		
A3	05/29/15	ECO #15-029	H. MA	W. Cook		

MPS88X-x000

x = plating option (1 or 5)

Modular Plug, Shielded, RoHS Compliant

8 Position, 8 Contact



UNITS
mm