



MODULAR JACKS AND PLUGS: GLX Series
Right Angle Modular Jack

Product Features

- 0.570" Height
- Snap-In Board Retention Tabs
- Available in 4, 6, 8 and 10 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

Performance Specifications

Materials and Finish

- Housing Material**
PBT Thermoplastic, UL 94V-0 Rated
- Contact Material**
Phosphor Bronze

Electrical Characteristics

- Insulation Resistance**
500 Megohms Min.
- Dielectric Withstanding Voltage**
1000V RMS, 60Hz
- Contact Resistance**
20 milliohms Max.
- Current Rating**
1.5A
- Voltage Rating**
125V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Part Number Builder

-
 Series Shield Option Positions & Contacts Body Options Color Option

Series

GLX - Right Angle Modular Jack

Shield Options

- N - Non-Shielded without Panel Stops
- S - Shielded without Panel Stops (8 and 10 Position only)

Number of Positions / Contacts

- 44 - 4 Positions / 4 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts
- 88 - 8 Positions / 8 Contacts (Only S Option)
- 1010 - 10 Positions / 10 Contacts (Only S Option)

Body Option

M - Short Body

Color Option

- Blank - Gray
- BLK - Black

Contact Kycon for Other Options

GLX Series

Dimensions in mm

GLX-N-44M

