



DC POWER CONNECTORS: KLDLX Series

Right Angle Panel Mount DC Power Jack

Product Features

- 2.0mm and 2.5mm Pin Options
- Panel Mount
- Solder Eyelets
- Built in DC On/Off Switch
- Full metal shell for increased strength
- Locks when used with the KLDLX-P Series

Performance Specifications

Materials and Finish

- Housing:** PBT Thermoplastic, UL94V-0 Rated, Black Color
- Center Pin & Threaded Barrel:** Brass, Nickel Plated
- Contact #1, #3:** Brass, Silver Plated
- Contact #2:** Phosphor Bronze, Silver Plated
- Nut:** Brass, Cu/Sn Plated
- Washer:** SPCC, Nickel Plated

Electrical Characteristics

- Rated Current:** 5A
- Rated Voltage:** 24V DC
- Insulation Resistance:** 100 Megohms Min. at 500V DC
- Contact Resistance:** 30 milliohms Max.
- Dielectric Withstanding Voltage:** 500V AC for 1 Minute
- Recommended Minimum Panel Thickness:** 1.5mm


Mechanical Characteristics

- Durability Test:** 5000 Cycles
- Insertion Force:** 3.0kg Max.
- Extraction Force:** 0.3kg Min.
- Operating Temperature:** -25°C to +70°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder



Series

KLDLX-0202 - Panel Mount DC Power Jack

Diameter

- A - 2.0mm Center Pin Diameter
- B - 2.5mm Center Pin Diameter

Contact Kycon For Other Options

KLDLX Series

Dimensions in mm

